

TPA Series Gantry Plug Parking Adaptors

Liquip offers the TPA series truck plug parking adaptors to suit both 3 or 4 pin bayonet fastening (J-slots) gantry plugs. The TPA series adaptors are supplied with a provision to mount and adjust a proximity switch.

TPA gantry plug parking adaptors provide a safe electronic interlock that can be utilised with the terminal automation system (TAS) to ensure the gantry plug has been disconnected from the loading vehicle before permission to leave the gantry in granted.



TPA4 - 4 Pin parking adaptor shown

Operation Instructions

Mount the parking adaptor in close proximity to the gantry monitor so that when parking the loop of the gantry plug wire is free and is not interfering with normal operations.

A suitable proximity switch is fixed inside the parking adaptor, when the gantry plug is disconnected from the loading vehicle it is connected to the parking adaptor.

When the gantry plug is connected the proximity switch reads and sends a signal which can be used in various ways


Ordering Information

TPA3: 3 Pin parking adaptor **TPA4**: 4 Pin parking adaptor

Specifications

Mounting	Acetal mounting blocks
Technical Data	 3 and 4 bayonet fixing to industry standard. Proximity switch size M30 x 1.5 thread specification to customer requirements. Conduit ports M20 x 1.5 thread, two options. Mounting by 2 stainless steel bolts (8mm diameter).
Variants	TP103 - 3 pin bayonet fastening TP104 - 4 pin bayonet fastening. Use also for 2 pin.
Weight	1.3kg
Materials	Stainless steel nose cone Acetal mounting block Aluminium body and cover plate PVC cap. Order separately, see below.
Associated equipment	5069 PVC cap TP103 - 3 Pin Truck Plug TP104 - 4 Pin Truck Plug GP100 series Gantry plugs

Page 1



www.liquip.com

M:\Product-Info\TPxxx\8-Sales\TPA Series Datasheet.pdf

Issue: F

5/12/23

Page 2